

Product Performance (cont)

Impact Product Performance Data

Call Size	Product	Product Description	A440-08 Performance Rating
Eagle Axiom® Casement			
3060	clad casement vent	HarborMaster® IG - ASTM Certified	DP +55, -65
3060	clad casement vent	HarborMaster Monolithic - TAS Certified	DP +65, -75
4060	1-piece fixed clad casement	HarborMaster IG - ASTM Certified	DP +70, -80
5080	1-piece fixed clad casement	HarborMaster Monolithic - TAS Certified	DP +70, -80
Eagle Axiom® Awning			
4030	clad awning vent	HarborMaster IG - ASTM Certified	DP +55, -65
4030	clad awning vent	HarborMaster Monolithic - TAS Certified	DP +70, -80
Auxiliary Window			
5080	clad fixed auxiliary	HarborMaster IG - ASTM Certified	DP +55, -65
5080	clad fixed auxiliary	HarborMaster Monolithic - TAS Certified	DP +70, -80
Talon® Double-Hung			
3466	clad double-hung vent	HarborMaster IG - ASTM Certified	DP +55, -55
3466	clad double-hung vent	HarborMaster Monolithic - TAS Certified	DP +55, -65
5066	clad fixed double-hung	HarborMaster IG - ASTM Certified	DP +55, -55
5066	clad fixed double-hung	HarborMaster Monolithic - TAS Certified	DP +55, -65
4020	clad double-hung transom	HarborMaster IG - ASTM Certified	DP +55, -65
4020	clad double-hung transom	HarborMaster Monolithic - TAS Certified	DP +55, -65
Ascent® Sliding Door			
6080	clad sliding French door	HarborMaster IG - ASTM Certified	DP +60, -65
3080	clad sliding French door sidelite	HarborMaster IG - ASTM Certified	DP +60, -65
6080	clad sliding French door	HarborMaster Monolithic - TAS Certified	DP +60, -65
3080	clad sliding French door sidelite	HarborMaster Monolithic - TAS Certified	DP +60, -65
Ascent® Outswing Door			
6080	clad outswing door	HarborMaster IG - ASTM Certified	DP +65, -65
3080	clad outswing door	HarborMaster IG - ASTM Certified	DP +65, -65
3080	clad outswing door	HarborMaster Monolithic - TAS Certified	DP +60, -75
6080	clad outswing door	HarborMaster Monolithic - TAS Certified	DP +60, -65
3080	clad outswing door sidelite	HarborMaster Monolithic - TAS Certified	DP +60, -75
Ascent® Inswing Door			
3080	clad inswing door	HarborMaster IG - ASTM Certified	DP +45, -65
6080	clad inswing door	HarborMaster IG - ASTM Certified	DP +40, -65
3080	clad inswing sidelite	HarborMaster IG - ASTM Certified	DP +45, -65

An asterisk (*) added to the primary designator indicates that the tested specimen was smaller, in either width or height, than the gateway test size as indicated in the 101/I.S. 2/A440 specification for the indicated product type and performance class.

"Performance Grade (PG)" ratings may vary from tested performance rating for larger or smaller units of a particular type.

Where designated, Eagle products are certified and labeled to the requirements of the Hallmark Certification Program. Actual performance may vary based on variations in manufacturing, shipping, installation, environmental conditions and conditions of use.

This data is accurate as of 09/11. Due to ongoing product changes, updated test results, or new industry standards, this data may change over time.

Contact your Eagle dealer or go to EagleWindow.com for more information.