

Call Size	Width (Inches)	Height (Inches)	Radius (Inches)	Meets Egress Req.	Sq. Ft. Clear Opening	Clear Opening (Inches)		Sq. Ft. Vent	Sq. Ft. Daylight Opening	Bottom Sash Glass Size (Inches)		Floor to Sill Height (Inches)
						Width	Height			Width	Height	
2030-2	48	36	72	No	1.22	19 11/16	9	1.22	2.91	17 15/16	14	49 7/16
2034-2	48	40	72	No	1.50	19 11/16	11	1.50	3.38	17 15/16	16	45 7/16
2040-2	48	48	72	No	2.05	19 11/16	15	2.05	4.32	17 15/16	20	37 7/16
2046-2	48	54	72	No	2.46	19 11/16	18	2.46	5.02	17 15/16	23	31 7/16
2049-2	48	57	72	No	2.66	19 11/16	19	2.66	5.38	17 15/16	24 1/2	28 7/16
2050-2	48	60	72	No	2.87	19 11/16	21	2.87	5.73	17 15/16	26	25 7/16
2056-2	48	66	72	No	3.28	19 11/16	24	3.28	6.43	17 15/16	29	19 7/16
2060-2	48	72	72	No	3.69	19 11/16	27	3.69	7.14	17 15/16	32	13 7/16
2430-2	56	36	72	No	1.23	23 11/16	7 1/2	1.23	3.53	21 15/16	14	49 7/16
2434-2	56	40	72	No	1.56	23 11/16	9 1/2	1.56	4.11	21 15/16	16	45 7/16
2440-2	56	48	72	No	2.22	23 11/16	13 1/2	2.22	5.27	21 15/16	20	37 7/16
2446-2	56	54	72	No	2.71	23 11/16	16 1/2	2.71	6.14	21 15/16	23	31 7/16
2449-2	56	57	72	No	2.96	23 11/16	18	2.96	6.58	21 15/16	24 1/2	28 7/16
2450-2	56	60	72	No	3.21	23 11/16	19 1/2	3.21	7.02	21 15/16	26	25 7/16
2456-2	56	66	72	No	3.70	23 11/16	22 1/2	3.70	7.89	21 15/16	29	19 7/16
2460-2	56	72	72	No	4.19	23 11/16	25 1/2	4.19	8.76	21 15/16	32	13 7/16
2630-2	60	36	72	No	1.19	25 11/16	6 21/32	1.19	3.82	23 15/16	14	49 7/16
2634-2	60	40	72	No	1.54	25 11/16	8 21/32	1.54	4.46	23 15/16	16	45 7/16
2640-2	60	48	72	No	2.26	25 11/16	12 21/32	2.26	5.73	23 15/16	20	37 7/16
2646-2	60	54	72	No	2.79	25 11/16	15 21/32	2.79	6.69	23 15/16	23	31 7/16
2649-2	60	57	72	No	3.06	25 11/16	17 5/32	3.06	7.17	23 15/16	24 1/2	28 7/16
2650-2	60	60	72	No	3.33	25 11/16	18 21/32	3.33	7.64	23 15/16	26	25 7/16
2656-2	60	66	72	No	3.86	25 11/16	21 21/32	3.86	8.60	23 15/16	29	19 7/16
2660-2	60	72	72	No	4.40	25 11/16	24 21/32	4.40	9.56	23 15/16	32	13 7/16
2830-2	64	36	72	No	1.10	27 11/16	5 3/4	1.10	4.10	25 15/16	14	49 7/16
2834-2	64	40	72	No	1.49	27 11/16	7 3/4	1.49	4.80	25 15/16	16	45 7/16
2840-2	64	48	72	No	2.26	27 11/16	11 3/4	2.26	6.18	25 15/16	20	37 7/16
2846-2	64	54	72	No	2.83	27 11/16	14 3/4	2.83	7.22	25 15/16	23	31 7/16
2849-2	64	57	72	No	3.12	27 11/16	16 1/4	3.12	7.74	25 15/16	24 1/2	28 7/16
2850-2	64	60	72	No	3.41	27 11/16	17 3/4	3.41	8.26	25 15/16	26	25 7/16
2856-2	64	66	72	No	3.99	27 11/16	20 3/4	3.99	9.30	25 15/16	29	19 7/16
2860-2	64	72	72	No	4.57	27 11/16	23 3/4	4.57	10.34	25 15/16	32	13 7/16
3030-2	72	36	72	No	0.81	31 11/16	3 11/16	0.81	4.63	29 15/16	14	49 7/16
3034-2	72	40	72	No	1.25	31 11/16	5 11/16	1.25	5.44	29 15/16	16	45 7/16
3040-2	72	48	72	No	2.13	31 11/16	9 11/16	2.13	7.04	29 15/16	20	37 7/16
3046-2	72	54	72	No	2.79	31 11/16	12 11/16	2.79	8.25	29 15/16	23	31 7/16
3049-2	72	57	72	No	3.12	31 11/16	14 3/16	3.12	8.85	29 15/16	24 1/2	28 7/16
3050-2	72	60	72	No	3.45	31 11/16	15 11/16	3.45	9.45	29 15/16	26	25 7/16
3056-2	72	66	72	No	4.11	31 11/16	18 11/16	4.11	10.66	29 15/16	29	19 7/16
3060-2	72	72	72	No	4.77	31 11/16	21 11/16	4.77	11.87	29 15/16	32	13 7/16

Notes:

Floor to sill height is based on structural header heights of 6' 10-1/2" and is calculated from the top of the subfloor to the top of the inside sill stop.

Egress Requirements: 5.7 sq. ft. minimum clear opening area, 20" minimum clear opening width, 24" minimum clear opening height, 44" maximum floor to sill height.

Code restrictions may vary depending on your local building codes.

If glass is positioned within 18" of the floor, safety/tempered glass may be required by code.

Clear Opening / Daylight / Vent numbers are for each unit

Eagle Window & Door reserves the right to change specifications without notice.